

---



---

**PACHIN 226**


---



---

<b>Description:</b>	<b>Fire retardant paint. Based on acrylic emulsion and special pigments.</b>
<b>Advantages:</b>	<ul style="list-style-type: none"> <li>• Alkali resistance.</li> <li>• Washable.</li> <li>• Anti - chalking.</li> <li>• With no smell.</li> <li>• Very good adhesion.</li> <li>• Fire retardant.</li> <li>• Thinning by water.</li> <li>• Friend to environment.</li> <li>• Flow and easy to use.</li> </ul>
<b>Fields of application:</b>	<ul style="list-style-type: none"> <li>• Used as a finishing coat on concrete, wood, steel surfaces.</li> </ul>
<b>Color</b>	As PACHIN shades.
<b>Finish</b>	Matt.
<b>Specific gravity:</b>	1.3 ± 0.1 gm / cm <sup>3</sup>
<b>Solid by volume:</b>	50 %.
<b>Theoretical spreading rate:</b>	4 m <sup>2</sup> / kg (at D.F.T 100 micron).
<b>Wet film thickness:</b>	100 micron.
<b>dry film thickness:</b>	50 micron.
<b>Drying time:</b>	<ul style="list-style-type: none"> <li>• Surface: 30 minutes (at 25°C &amp; 60% R.H.).</li> <li>• Complete: 1 hr. (at 25°C &amp; 60% R.H.).</li> </ul>
<b>Time to recoat:</b>	<ul style="list-style-type: none"> <li>• min.: 3 - 4 hrs. (at 25°C &amp; 60% R.H.).</li> <li>• max.: no limit.</li> </ul>
<b>Shelf life:</b>	12 months in its closed original cans at good stores in ideal conditions.
<b>Thinner:</b>	By water (5 - 10 %).
<b>Method of application:</b>	<ul style="list-style-type: none"> <li>• By airless spray.</li> <li>• By air spray.</li> <li>• By brush or roller.</li> </ul>
<b>Surface preparation:</b>	<ul style="list-style-type: none"> <li>• The surface should be dry and clean from dirties, oils, and greases, it should be applied on primer pachin 225 (400 micron).</li> <li>• The dry film thickness of pachin 226 should be (600 micron).</li> </ul>