
ANTI FOULING NO. 10435

Description:	It is an anti - fouling paint based on modified alkyd, pigmented with zinc chromate.
Advantages:	<ul style="list-style-type: none"> • Anti - fouling paint. • Good adhesion. • High elasticity.
Fields of application:	<ul style="list-style-type: none"> • Used on painting immersed and non - immersed surfaces in ships and boats. • Excellent to be used in marines fields.
Color	Brown / blue.
Finish	Eggshell.
Theoretical spreading rate:	3 m ² /kg at D.F.T 100 m
Drying time:	<ul style="list-style-type: none"> • Surface: 3 - 4 hrs. (at 25°C & 60% R.H.). • Complete: 24 hrs. (at 25°C & 60% R.H.).
Time to recoat:	<ul style="list-style-type: none"> • Min.: 8 hrs (at 25°C & 60% R.H.). • Max.: no limit.
Shelf life:	12 months in its closed original cans at good stores in ideal conditions.
Thinner:	No. 11500 (PACHIN thinner).
Method of application:	<ul style="list-style-type: none"> • By air spray: Volume of thinner: 0 - 10 % Nozzle orifice: 3.3 mm Nozzle pressure: 3 - 4 bar • By brush or roller: Volume of thinner: 0 - 5 %
Surface preparation:	<ul style="list-style-type: none"> • The surface should be dry and clean from dirties, oils and greases, it should be applied on primed metal surfaces.