
MATT BITUMINOUS PAINT 11340

Description:	It is a high quality matt bitumen paint.
Advantages:	<ul style="list-style-type: none"> • Very good adhesion. • Flow and easy to use. • Medium viscosity. • Very high spreading rate. • Very good water resistant finishing coat.
Fields of application:	<ul style="list-style-type: none"> • Used specially in water ballast, tanks.
Color	Black.
Finish	Matt.
Specific gravity:	1.00 ± 0.1 gm / cm ³
Solid by volume:	60 % (approx.).
Theoretical spreading rate:	10 - 12 m ² / kg (at D.F.T 50 micron).
Drying time:	<ul style="list-style-type: none"> • Surface: 3 - 4 hrs. (at 25°C & 60% R.H.). • Complete: 24 hrs. (at 25°C & 60% R.H.).
Time to recoat:	<ul style="list-style-type: none"> • Min.: 24 hrs (at 25°C & 60% R.H.). • Max.: no limit.
Shelf life:	12 months in its closed original cans at good stores in ideal conditions.
Thinner:	PACHIN 11500.
Method of application:	<ul style="list-style-type: none"> • By air spray: Volume of thinner: 1 - 5 % Nozzle orifice: 2 - 3 mm Nozzle pressure: 3 - 4 bar • By brush and roller: (for small areas) Volume of thinner: 5 - 10 %
Surface preparation:	<ul style="list-style-type: none"> • For new steel: Sand blasting to Sa 2½ or steel brush to get clean surface condition. • For maintenance: remove dust, oil and grease by wet or dried abrasive or power tool cleaning.